



HT-D-17



1. Conversion to the right voltage.
2. Stabilization of the voltage.
3. Compact size design.
4. Efficient cooling (thermal controlled) fan.



SPECIFICATION

Model No.:	HT-D-17
INPUT SPECIFICATIONS	
Nominal input voltage:	24V
Input range:	18~33VDC(±1V)
No load consumption:	0.03A(±0.5%)
OUTPUT SPECIFICATIONS	
Nominal voltage:	12.5V(±0.5V)
Voltage range:	12V~13V(±0.5V)
Ripple:	<1%
Maximum power:	25A(±1A)
Nominal power:	17A(±1A)
PROTECTIONS	
Over current:	yes
Over heat:	yes
SAFETY&EMC	
EMC:	EN61000-6-4 : 2007, CISPR 11 : 2003 Class B, EN61000-6-2 : 2005, IEC 61000-4-2 : 1995+A1 : 1998+A2: 2000, IEC61000-4-3 : 2008, IEC61000-4-8 : 1993+A1: 2000.
LVD:	Compliance to EN60950
GENERAL SPECIFICATIONS	
Working temp.:	-15°C~+45°C
Working humidity:	20%~90% RH non-condensing
Storage temp., humidity:	-30~+70°C/-22°F~+158°F, 10~95% RH
Temp.coefficientI:	±0.05%°C(0~55°C)
Efficiency:	>85%
Dimension(LxWxH):	178x89x50mm
Net weight:	0.6kgs